

Protectowire Linear Heat Detector

TYPE EPC – VINYL JACKET



PHSC-155-EPC 155° (68°C)
Max. Recommended Ambient Temp 100° F (38° C)



PHSC-190-EPC 190° (88°C)
Max. Recommended Ambient Temp 150° F (66° C)



PHSC-220-EPC 220° (105°C)
Max. Recommended Ambient Temp 175° F (79° C)



PHSC-280-EPC 280° (138°C)
Max. Recommended Ambient Temp 200° F (93° C)



PHSC-356-EPC 356° (180°C)
Max. Recommended Ambient Temp 221° F (105° C)

TRI-WIRE™ DUAL TEMPERATURE VINYL JACKET



PHSC-6893-TRI 155°/200° (68°/93°C)
Max. Recommended Ambient Temp 100° F (38° C)

TYPE XCR FLUOROPOLYMER JACKET



PHSC-155-XCR 155° (68°C)
Max. Recommended Ambient Temp 100°F (38°C)



PHSC-190-XCR 190° (88°C)
Max. Recommended Ambient Temp 150°F (66°C)



PHSC-220-XCR 220° (105°C)
Max. Recommended Ambient Temp 175°F (79°C)



PHSC-280-XCR 280° (138°C)
Max. Recommended Ambient Temp 200°F (93°C)



PHSC-356-XCR 356° (180°C)
Max. Recommended Ambient Temp 250°F (121°C)

TYPE EPR – POLYPROPYLENE ELASTOMER JACKET



PHSC-155-EPR 155° (68°C)
Max. Recommended Ambient Temp 100° F (38° C)

PHSC-190-EPR 190° (88°C)
Max. Recommended Ambient Temp 150° F (66° C)

PHSC-280-EPR 280° (138°C)
Max. Recommended Ambient Temp 200° F (93° C)

PHSC-356-EPR 356° (180°C)
Max. Recommended Ambient Temp 250° F (121° C)

TYPE XLT – PROPRIETARY POLYMER JACKET



PHSC-135-XLT 135° (57°C)
Max. Recommended Ambient Temp 100° F (38° C)

Installation hardware

