

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### F0211-300, F0222-300, F0213-300, F0233-300, F0212-300

Resilient Seated Gate Valves. Available with an indicator post flange. Rated Working Pressure 300 psi (2070 kPa). Available with the end connections listed below:

Model No.	Size in. (mm)	End Connections
F0211-300	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange x Flange (ANSI, ISO, JIS)
F0222-300	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove x Groove (ANSI, ISO, JIS)
F0213-300	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange x Mechanical Joint
F0233-300	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 00, 125, 150, 200, 250 and 300)	Mechanical Joint
F0212-300	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange x Groove (ANSI, ISO, JIS)

<b>Company Name:</b>	Weflo Valve Company Ltd
<b>Company Address:</b>	145-157 St. John St, London EC1V 4PY, United Kingdom
<b>Company Website:</b>	<a href="http://www.weflovalve.com">http://www.weflovalve.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved