## William J. Clinton Presidential Center and Library

Visitors to the new William J. Clinton Presidential Library and Museum will see a number of interesting things, but one thing they won't see is the advanced smoke detection system from Xtralis. William J. Clinton
Presidential Library and Museum
The centre offers an interactive
educational centre displaying memorabilia
from President Clinton's term in office.

Size: 40 employees

Location: Little Rock, Arkansas, USA www.clintonlibrary.gov

**Industry** Archives

Products used 2 x VESDA LaserSCANNER

Cantilevered over the Arkansas River to symbolize a "bridge to the 21st century," Bill Clinton's presidential library contains historical documents and memorabilia that will grow more valuable with time.

The \$165 million William Jefferson Clinton Presidential Center and Library, in Little Rock, Arkansas, opened its doors to the public in November 2004. Exhibits about President Clinton's two terms in office include a replica of the Oval Office and interactive exhibits, but one thing visitors will not see is a high-tech smoke detection system that protects the library's most important archives.

The highly sensitive but inconspicuous VESDA® LaserSCANNER™ air sampling smoke detection system was chosen for the library's three records rooms, which are accessible to researchers by permission only. The rooms' vault-like walls are designed to hold off an outside fire for four hours. The VESDA equipment is designed to detect an inside fire at the earliest (incipient) stage before smoke is visible to human eyes. Display panels in the building's security office and at two information desks would give guards the earliest possible warning—early enough for them to find and control a potential fire source before smoke damaged the contents of the library or flames set off the sprinkler system. The hundreds of gallons of water released by the sprinklers would extinguish a fire but could ruin the documents.

When his employer, Cromwell Architects Engineers, was awarded the engineering contract for the Clinton Center, Fire Protection Engineer Scott Lacey specified the LaserSCANNER.





## **VESDA**<sup>®</sup> ...Customer success story

"I had previously used VESDA systems for a number of different facilities and was very satisfied with their performance," he says. "At one large computer data facility, a VESDA system alerted the maintenance staff to a problem and they found the source on the other side of the building — a capacitor on one of their emergency generators was going bad. They found it before a fire broke out or any fire suppression systems were activated."

Compatible with standard fire alarm panels, every VESDA system can be programmed at installation to achieve the desired sensitivity, without nuisance alarms.

According to Xtralis, "Two independent VESDA LaserSCANNER detectors cover the rooms, which are divided into eight zones. The detectors actively and continuously monitor the air, looking for any presence of smoke. High-efficiency aspirators draw air from 68 sampling points to the detectors via a network of VESDA fire-resistant CPVC piping (UL 1887 listed for use in Plenum-rated areas). The pipes are painted white to match the color of the concrete waffle-style ceiling."

While highly sensitive, the VESDA detectors have several built-in features to virtually eliminate nuisance alarms that plague other methods of detection. AutoLearn™ and Referencing functionality built into the detectors prevents nuisance alarms by automatically adjusting the background levels to allow for changing ambient air conditions and external pollution.

VESDA systems are also easy to maintain, saving the library time and money. Detectors can be serviced at an accessible level, eliminating the need to reach the ceiling and thus eliminating the need to erect scaffolding.

To make sure the LaserSCANNER system was appropriate for the Clinton Center, Lacey used ASPIRE™, computer modeling software for evaluating VESDA pipe system layouts. By entering parameters such as pipe length, air temperature, and aspirator pressure, ASPIRE can predict the performance of a proposed pipe network.

"I ended up calling VESDA tech support numerous times," Lacey recalls, "just to run things by them and verify that I was doing the calculations properly. They were as cooperative as they could be. To me, VESDA was the obvious choice as soon as I saw the plans, but I had to prove it would work. It all came together, and once again I am pleased with the high level of quality and professionalism that VESDA delivers."



obvious choice as soon as I saw the plans, but I had to prove it would work. It all came together, and once again I am pleased with the high level of quality and professionalism that VESDA delivers.

Scott Lacey
Fire Protection Engineer
Cromwell Architects Engineers

## www.xtralis.com

The Americas +1 781 740 2223 Asia +852 2297 2438 Australia and New Zealand +61 3 9936 7000 Continental Europe +41 55 285 99 99 UK and the Middle East +44 1442 242 330

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

This document includes registered and unregistered trademarks. All trademarks displayed are the trademarks of their respective owners. Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label. This document is subject to copyright owned by Xtralls AG ("Xtralls"). You agree not to copy, communicate to the public, adapt, distribute, transfer, sell, modify or publish any contents of this document without the express prior written consent of Xtralis.

Document: 11483 01

