

Xtralis VESDA VLF

VLF-250



Features

- Swift-Start™ Operation
- SonicFlow™ (Ultrasonic Airflow Sensing)
- Laser-Based Absolute Smoke Detection
- Pre-engineered Pipe Network Designs
- Programmable Alarm Thresholds
- Clean air barrier optics protection
- Instant Recognition Display
- Instant Fault Finder™
- AutoLearn™ Smoke
- AutoLearn™ Flow
- Field Service Access Door
- Multiple Event Logging in separate logs
- Event log – up to 18,000 events
- Offline/online configuration capability
- Up to 2500 sq. ft. (250 m²) coverage

The Xtralis VESDA VLF-250 Air Sampling Smoke Detector provides very early warning smoke detection performance for the protection of small, business-critical environments of 2500 sq. ft. or less.

The air sampling detection concept works by continually drawing ambient air through sampling holes in a pipe network. Upon entering the unit the sampled air is filtered and passed into the detection chamber where light scattering technology detects the presence of very small amounts of smoke. As the amount of detected smoke increases the revolutionary circular Smoke Dial™ provides the user with an instant understanding of a smoke event, even from a significant distance. Detector status information is communicated externally via relays or optional interface cards.

Swift Start™

The unrivalled “Swift-Start” concept provides straight-forward installation and commissioning right out of the box using proven pre-engineered sampling pipe network designs and powerful AutoLearn routines without the need for a special interface or software programming tools. The AutoLearn™ function automatically sets acceptable alarm thresholds for both smoke and flow levels without the need for a PC or separate programming device. Custom sampling pipe network designs are supported via the ASPIRE2 calculation program.

In operation, the unique circular Smoke Dial provides instant understanding of a smoke event and system status. Should a fault occur the System Fault LED is illuminated. To troubleshoot the condition the user simply opens the field service door and activates the Instant Fault Finder feature to determine the specific fault condition. This information can then be passed onto their Fire Service provider, ensuring service technicians arrive onsite fully prepared.

SonicFlow™ Feature

The Ultrasonic Flow Sensing (patent pending) used in the VLF provides a direct reading of the sampling pipe airflow rate. The SonicFlow concept is immune to air temperature and pressure changes and is unaffected by contamination. The VLF is the first air sampling smoke detector to use ultrasonic flow sensing.

Listings/Approvals

- UL
- ULC
- FM
- CFE
- LPCB
- VdS
- VNIPO
- AFNOR
- ActivFire
- CE - EMC and CPD
- EN 54-20

Regional approvals listings and regulatory compliance vary between Xtralis VESDA product models. Refer to www.xtralis.com for the latest product approvals matrix.



Specifications

Input Power

Voltage: 24V DC Nominal (18-30 V DC)
 Current @ 24 VDC: 220 mA nominal, 295 mA in alarm

Dimensions (W x H x D) 97¹/₈ in x 7¹/₈ in x 3¹/₂ in (255 mm x 185 mm x 90 mm)

Weight Approx. 4.4 lbs (2 kg)

IP Rating IP30

Mounting Upright, inverted or horizontal

Operating Conditions

Detector Ambient: 32 °F to 104 °F (0 °C to 40 °C)

Humidity: 5% to 95% (non-condensing)

Sampling Network

Maximum area of coverage: 2,500 sq. ft depending on local codes and standards.

Maximum Pipe length in accordance with pre-engineered designs or for custom networks use Pipe Modelling Design Tool (ASPIRE2™) and NFPA standards.

Air Inlet Pipe

Accepts both metric and American standard pipe sizes.

American Pipe: ¼ inch I.D Metric: 25 mm O.D.

Relay Outputs

3 Form C relays (Fire 1, Action, Fault), Contacts rated 2A @ 30 VDC (max).

Cable Access

3 x 1 in. (25 mm) cable entries (1 rear entry, 2 top entry)

Cable Termination

Screw Terminals 30-12AWG (0.2-2.5 mm²)

Interfaces

Shown in Terminal Block Connections diagram, to right, plus an RS232 Programming Port.

General Purpose Input (GPI) interface offers: Reset, Disable, Standby, Alarm set 1, Alarm set 2 and External Input functions.

Sensitivity Range: 0.008 - 6.25 % obs/ft (0.025 - 20.00 % obs/m)

Alarm Threshold Setting Range

Alert, Action 0.008 - 0.625 % obs/ft (0.025 - 2.00 % obs/m)

Fire 1, Fire 2 0.008 - 6.25 % obs/ft (0.025 - 20.00 % obs/m)

Individual Alarm Delays 0 – 60 seconds

Two Alarm Threshold Settings Either time or GPI based

Display

- 4 Alarm State Indicators
- Smoke Level Indicator
- Reset, Disable and Test Controls
- Fault and Disabled Indicators
- Instant Fault Finder
- Smoke and Flow AutoLearn Controls

Event Log

Up to 18,000 events, time and date stamped in separate, non-volatile, logs for: Smoke Level, Flow Level, Detector Status and Faults

AutoLearn Smoke & Flow

- Automatically set acceptable alarm thresholds for both smoke and flow levels
- Minimum 15 minutes, maximum 15 days (default 14 days)
- During AutoLearn thresholds are NOT changed from pre-set values

Warranty Period

2 years

Ordering Information:

- VLF-250-00 Xtralis VESDA VLF-250
- VSP-005 Filter Cartridge
- VIC-010 VESDAnet Interface Card
- VIC-020 Multifunction Control Card (MCC)
- VIC-030 Multifunction Control Card (MCC) c/w Monitored Power Output (MPO)
- VSP-722 Aspirator for VLF-250

www.xtralis.com

The Americas +1 781 740 2223 **Asia** +852 2916 8894 **Australia and New Zealand** +61 3 9936 7000
Continental Europe +32 56 24 19 51 **UK and the Middle East** +44 1442 242 330

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

This document includes registered and unregistered trademarks. All trademarks displayed are the trademarks of their respective owners. Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label.

This document is subject to copyright owned by Xtralis AG ("Xtralis"). You agree not to copy, communicate to the public, adapt, distribute, transfer, sell, modify or publish any contents of this document without the express prior written consent of Xtralis.

Doc. no. 07844_09

Part: 20489

Display

The display provided to the user includes a Smoke Dial and alarm and status indicators.




When the field service access door is open, the user has access to the RESET, DISABLE, Fire Test, AutoLearn and Instant Fault Finder functions.

When the Instant Fault Finder function is activated, the Smoke Dial converts to a fault indicator, with the dial segment numbers corresponding to the faults listed below.

Legend of fault indicators

- | | |
|-------------|-----------------------|
| 1 Filter | 6 External Device/PSU |
| 2 Aspirator | 7 Interface card |
| 3 High flow | 8 Field wiring |
| 4 Low flow | 9 AutoLearn Fail |
| 5 n/a | 10 Detector failure |

Terminal Block Connections



- | | |
|-------------------------|--|
| 1 GPI | |
| 2 GPI | |
| 3 Display TX | |
| 4 Display RX | |
| 5 Display Common Ground | |
| 6 Display Power - | |
| 7 Display Power + | |
| 8 Power Return 0 VDC | From power supply unit |
| 9 Power In 24 VDC | |
| 10 Power Return 0 VDC | To next detector (if more than 1 detector per Power Supply Unit) |
| 11 Power Out 24 VDC | |
| 12 NC | |
| 13 Common | Fault relay |
| 14 NO | |
| 15 NC | |
| 16 Common | Action relay |
| 17 NO | |
| 18 NC | |
| 19 Common | Fire 1 relay |
| 20 NO | |

Approvals Compliance

Please refer to the Product Guide for details regarding compliant design, installation and commissioning.

